




						
	LEO13GT	LEO15GT	LEO18GTplus	LEO23GT	LEO24GT	LEO24T
Type de fleche Boom Type	Articulée Articulating	Articulée Articulating	Articulée Articulating	Articulée Articulating	Articulée Articulating	Télescopique Straight
Hauteur de travail Working height	12,75 m	14,70 m	18,30 m	23,00 m	24,00 m	24,00 m
Déport Horizontal outreach	6,05 m	7,60 m	8,50 m	11,20 m	10,20 m (250 kg) 12,80 m (100 kg)	12,00 m (250 kg) 14,00 m (100 kg)
Charge Panier Platform capacity	200 kg	200 kg	200 kg	200 kg	250 kg	250 kg
Dispositif de levage Lifting device	200 kg capacité/ capacity (optional)	200 kg capacité/ capacity (optional)	200 kg capacité/ capacity (optional)	-	300 kg capacité/ capacity (optional)	300 kg capacité/ capacity (optional)
Dimensions transport Transport measure	1,99 m x 0,78 m	1,99 m x 0,78 m	1,99 m x 0,78 m	1,97 m x 0,98 m	1,99 m x 0,89 m	1,99 m x 0,89 m
Poids Weight	1640 kg	2060 kg	2650 kg	2990 kg	2990 kg	2990 kg
Pendulaire Jib, movable	-	-	90°	-	165°	180°
Chenilles ajustables Adjustable tracks	-	-	Hydraulicquement Hydraulic	Hydraulicquement Hydraulic	Hydraulicquement Hydraulic	Hydraulicquement Hydraulic
Moteur électrique Electric drive	Standard	Standard	Standard	Standard	Standard	Standard
Moteur à essence Petrol engine	Standard	Standard	Standard	-	-	-
Moteur à Diesel Diesel engine	Optional	Optional	Standard	Standard	Standard	Standard
Batterie Battery drive	Optional	Optional	Optional	Optional	Optional	Optional
Commande filaire Cable control	Standard	Standard	-	Standard	-	-
Radiocommande Radio remote control	-	-	Standard	-	Standard	Standard
Coming Home Function	-	-	-	-	Standard	Standard
Fonction memoire Memory function	-	-	-	-	-	-



					
	LEO27GTplus	LEO30Tplus	LEO34GTplus	LEO35Tplus	LEO39GTplus
Type de fleche Boom Type	Articulée Articulating	Télescopique Straight	Articulée Articulating	Télescopique Straight	Articulée Articulating
Hauteur de travail Working height	27,00 m	30,00 m (300 kg) 27,00 m (400 kg)	34,10 m	35,00 m (300 kg) 32,00 m (400 kg)	38,60 m
Déport Horizontal outreach	12,50 m (250 kg) 14,30 m (100 kg)	12,70 m (400 kg) 14,00 m (300 kg) 16,00 m (140 kg)	18,00 m (400 kg) 18,90 m (300 kg) 19,90 m (140 kg)	13,00 m (400 kg) 14,00 m (300 kg) 16,00 m (140 kg)	18,30 m (400 kg) 20,20 m (300 kg) 23,30 m (140 kg)
Charge Panier Platform capacity	250 kg	400 kg	400 kg	400 kg	400 kg
Dispositif de levage Lifting device	300 kg capacité/ capacity (optional)	450 kg capacité/ capacity (optional)	450 kg capacité/ capacity (optional)	450 kg capacité/ capacity (optional)	450 kg capacité/ capacity (optional)
Dimensions transport Transport measure	1,99 m x 0,98 m	1,98 m x 1,58 m	1,99 m x 1,59 m	1,99 m x 1,58 m	1,99 m x 1,59 m
Poids Weight	3870 kg	4550 kg	8210 kg	5500 kg	8750 kg
Pendulaire Jib, movable	165°	180°	200°	180°	200°
Chenilles ajustables Adjustable tracks	Hydrauliquement Hydraulic	Hydrauliquement Hydraulic	Hydrauliquement Hydraulic	Hydrauliquement Hydraulic	Hydrauliquement Hydraulic
Moteur électrique Electric drive	Standard	Standard	Standard	Standard	Standard
Moteur à essence Petrol engine	-	-	-	-	-
Moteur à Diesel Diesel engine	Standard	Standard	Standard	Standard	Standard
Batterie Battery drive	Optional	Optional	-	Optional	-
Commande filaire Cable control	-	-	-	-	-
Radiocommande Radio remote control	Standard	Standard	Standard	Standard	Standard
Coming Home Function	Standard	Standard	Standard	Standard	Standard
Fonction memoire Memory function	-	Standard	Standard	Standard	Standard